1/17

Fig.1

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.:   Filed herewith   Atty Docket: IMEC282.001AUS

2/17

Fig.2

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith   Atty Docket: IMEC282.001AUS

3/17

Fig. 3

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith Atty Docket: IMEC282.001AUS

4/17

Fig. 4

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith   Atty Docket: IMEC282.001AUS

5/17

Fig. 5

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith   Atty Docket: IMEC282.001AUS

6/17

Fig. 6

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith   Atty Docket: IMEC282.001AUS

7/17

# of UT antenna	G^u	H^u	N^u	E^u	$H^u \cdot N_u$
2	2x2	2x8	8x4	4x2	2x4
3	2x3	3x8	8x2	2x2	3x2

Fig. 7

8/17

Fig. 8

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith Atty Docket: IMEC282.001AUS

9/17

Fig. 9

Fig. 10

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith Atty Docket: IMEC282.001AUS

11/17

Fig. 11

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith Atty Docket: IMEC282.001AUS

12/17

Fig. 12

13/17

Fig. 13

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith Atty Docket: IMEC282.001AUS

14/17

Fig. 14

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith   Atty Docket: IMEC282.001AUS

15/17

Fig. 15

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT
MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith   Atty Docket: IMEC282.001AUS

16/17

| BER	# users	5 degr. & 0.7 dB reciprocity mismatch	With calibration
10^{-2}	2	0.44 dB	0.04 dB
	3	1.48 dB	0.11 dB
	4	∞	1.30 dB
10^{-3}	2	1.02 dB	0.11 dB
	3	∞	0.49 dB
	4	∞	∞ (not targeted)

Fig. 16

METHOD AND APPARATUS FOR MULTI-USER MULTI-INPUT MULTI-OUTPUT TRANSMISSION
Bourdoux, et al.
Appl. No.: Filed herewith   Atty Docket: IMEC282.001AUS

17/17

Fig. 17